

Technical Data Sheet | ТН_ОТВЕРДИТЕЛИ ДЛЯ ПОЛИУРЕТАНОВ

Annula e sostituisce / Supersedes previous 07 January 2021

DATA / DATE 19 April 2021

Для получения информации о других характеристиках и способах использования, пожалуйста, обратитесь к техническим данным, касающимся части "А". Изоцианатные отвердители подвержены воздействию влаги, поэтому следует герметично закрывать упаковки и хранить их в сухом месте. После вскрытия упаковки продукт должен быть израсходован в течение того же дня.

АРТИКУЛ	СРОК ХРАНЕНИЯ	СУХОЙ ОСТАТОК	УДЕЛЬНАЯ ПЛОТНОСТЬ
	(месяцы)	%	кг/л
ТН0146/00	24	25 ± 1	0,986 ± 0,030
ТН0222/00	24	24 ± 1	0,965 ± 0,030
ТН0333/00	24	24 ± 1	0,965 ± 0,030
ТН0613/00	24	21 ± 1	0,930 ± 0,030
ТН0620/00	24	26 ± 1	0,955 ± 0,030
ТН0675/00	24	28 ± 1	0,950 ± 0,030
ТН0703/00	24	24 ± 1	0,955 ± 0,030
ТН0711/00	24	28 ± 1	0,940 ± 0,030
ТН0712/00	24	23 ± 1	0,960 ± 0,030
ТН0713/00	24	22 ± 1	0,930 ± 0,030
ТН0715/00	24	34 ± 1	0,970 ± 0,030
ТН0718/00	24	28 ± 1	0,940 ± 0,030
ТН0720/00	24	26 ± 1	0,955 ± 0,030
ТН0721/00	24	44 ± 1	1,000 ± 0,030
ТН0722/00	24	29 ± 1	0,969 ± 0,030
ТН0723/00	24	21 ± 1	0,914 ± 0,030
ТН0724/00	24	31 ± 1	0,950 ± 0,030

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.

COMPANY WITH
MANAGEMENT SYSTEM
- UNI EN ISO 9001 -
- UNI EN ISO 14001 -

Sherwin-Williams Italy S.r.l. – con unico socio
Via del Fiffo, 12 - 40065 Pianoro (BO) - Italia - C.P. 18
tel. +39 051 770 511 - fax +39 051 777 437
www.sayerlack.com
Cod. Fisc. e Reg. Impr. Bo 08866930152
P. IVA: IT 00494251200 - R.E.A. n. 313180
Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531

Company under the direction and coordination of The Sherwin-Williams Company, USA

АРТИКУЛ	СРОК ХРАНЕНИЯ	СУХОЙ ОСТАТОК	УДЕЛЬНАЯ ПЛОТНОСТЬ
	(месяцы)	%	кг/л
TH0727/00	24	32 ± 1	0,967 ± 0,030
TH0728/00	24	30 ± 1	0,980 ± 0,030
TH0731/00	24	40 ± 1	0,984 ± 0,030
TH0733/00	24	49 ± 1	1,015 ± 0,030
TH0734/00	12	37 ± 1	1,007 ± 0,030
TH0735/00	24	44 ± 1	0,998 ± 0,030
TH0738/00	24	39 ± 1	1,000 ± 0,030
TH0744/00	24	49 ± 1	1,060 ± 0,030
TH0746/00	24	37 ± 1	1,020 ± 0,030
TH0748/00	24	28 ± 1	0,950 ± 0,030
TH0749/00	24	32 ± 1	0,950 ± 0,030
TH0755/00	24	27 ± 1	0,970 ± 0,030
TH0756/00	6	75 ± 3	1,170 ± 0,030
TH0759/00	24	24 ± 1	0,930 ± 0,030
TH0760/00	24	42 ± 1	1,012 ± 0,030
TH0761/00	24	50 ± 1	1,070 ± 0,030
TH0765/00	24	35 ± 1	0,982 ± 0,030
TH0767/00	24	23 ± 1	0,950 ± 0,030
TH0773/00	24	28 ± 1	0,940 ± 0,030
TH0775/00	24	28 ± 1	0,950 ± 0,030
TH0779/00	24	27 ± 1	0,970 ± 0,030
TH0780/00	24	28 ± 1	0,960 ± 0,030

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.

COMPANY WITH
MANAGEMENT SYSTEM
- UNI EN ISO 9001 -
- UNI EN ISO 14001 -

Sherwin-Williams Italy S.r.l. – con unico socio
Via del Fiffò, 12 - 40065 Pianoro (BO) - Italia - C.P. 18
tel. +39 051 770 511 - fax +39 051 777 437
www.sayerlack.com
Cod. Fisc. e Reg. Impr. Bo 08866930152
P. IVA: IT 00494251200 - R.E.A. n. 313180
Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531

Company under the direction and coordination of The Sherwin-Williams Company, USA

АРТИКУЛ	СРОК ХРАНЕНИЯ	СУХОЙ ОСТАТОК	УДЕЛЬНАЯ ПЛОТНОСТЬ
	(месяцы)	%	кг/л
TH0781/00	24	70 ± 2	1,150 ± 0,030
TH0784/00	24	29 ± 1	0,960 ± 0,030
TH0787/00	24	28 ± 1	0,950 ± 0,030
TH0788/00	24	34 ± 1	1,000 ± 0,030
TH0790/00	24	36 ± 1	0,950 ± 0,030
TH0793/00	24	25 ± 1	0,934 ± 0,030
TH0799/00	24	28 ± 1	0,948 ± 0,030
TH0801/00	24	24 ± 1	0,940 ± 0,030
TH0805/00	24	24 ± 1	0,940 ± 0,030
TH0808/00	24	24 ± 1	0,940 ± 0,030
TH0825/00	24	40 ± 1	0,980 ± 0,030
TH0908/00	24	80 ± 1	1,100 ± 0,030
TH0925/00	24	26 ± 1	0,960 ± 0,030
TH1400/00	24	50 ± 1	1,059 ± 0,030
TH2510/00	24	19 ± 1	0,893 ± 0,030
TH2513/00	24	31 ± 1	0,965 ± 0,030
TH2520/00	24	34 ± 1	0,940 ± 0,030
TH2526/00	24	27 ± 1	0,940 ± 0,030
TH2530/00	12	75 ± 1	1,070 ± 0,030
TH2533/00	24	27 ± 1	0,965 ± 0,030
TH2537/00	24	29 ± 1	1,020 ± 0,030
TH2569/00	24	18 ± 1	0,950 ± 0,030
TH2580/00	24	20 ± 1	1,001 ± 0,030
TH2587/00	24	20 ± 1	1,000 ± 0,030
TH3192/00	24	31 ± 1	0,990 ± 0,010
TH6367/00	24	24 ± 1	0,940 ± 0,030
TH7918/00	24	25 ± 1	0,940 ± 0,030

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.
WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.