SAYERLACK®
INNOVATIVE WOOD SOLUTIONS

COMPANY WITH
MANAGEMENT SYSTEM
- UNI EN ISO 9001 -
- UNI EN ISO 14001 -

Sherwin-Williams Italy S.r.l. – con unico socio
Via del Fiffo, 12 - 40065 Pianoro (BO) - Italia - C.P. 18
tel. +39 051 770 511 - fax +39 051 777 437
www.sayerlack.com
Cod. Fisc. e Reg. Impr. Bo 08866930152
P. IVA: IT 00494251200 - R.E.A. n. 313180
Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531

Company under the direction and coordination of The Sherwin-Williams Company, USA

Technical **Data Sheet**

THX _ ОТВЕРДИТЕЛИ ДЛЯ ПОЛИУРЕТАНОВ

Annulla e sostituisce / Supersedes previous 19 April 2021

DATA / DATE 16 July 2021

Для получения информации о других характеристиках и способах использования, пожалуйста, обратитесь к техническим данным, касающимся части А". Изоцианатные отвердители подвержены воздействию влаги, поэтому следует герметично закрывать упаковки и хранить их в сухом месте. После вскрытия упаковки продукт должен быть израсходован в течение того же дня.

АРТИКУЛ	СРОК ХРАНЕНИЯ	СУХОЙ ОСТАТОК	УДЕЛЬНАЯ ПЛОТНОСТЬ
	(месяцы)	%	кг/л
THL3073/00	24	27 ± 1	0,930 ± 0,030
THL3109/00	24	40 ± 1	0,985 ± 0,030
THL3163/00	24	35 ± 1	0,980 ± 0,030
THL3256/00	24	38 ± 1	0,970 ± 0,030
THL3348/00	24	28 ± 1	0,950 ± 0,030
THL3354/00	24	50 ± 1	1,001 ± 0,030
THL3355/00	24	19 ± 1	0,893 ± 0,030
THL3364/00	24	24 ± 1	0,940 ± 0,030
THL3491/00	24	38 ± 1	1,004 ± 0,031
THL3508/00	24	32 ± 1	0,967 ± 0,030
THL3616/00	12	36 ± 1	0,992 ± 0,030
THL3625/00	24	23 ± 1	0,960 ± 0,030
THL3626/00	24	19 ± 1	0,893 ± 0,030
THL3627/00	24	36 ± 1	0,950 ± 0,030
THL3651/00	24	25 ± 1	0,934 ± 0,030
THL3752/00	12	22 ± 1	0,930 ± 0,030
THL3753/00	12	21 ± 1	0,930 ± 0,030
THL3825/00	12	21 ± 1	0,940 ± 0,030
THL3850/00	12	30 ± 1	0,970 ± 0,030
THL3852/00	12	24 ± 1	0,960 ± 0,030
THL3896/00	24	100	1,150 ± 0,030

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.
WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.

AZIENDA CON
SISTEMA DI GESTIONE
- UNI EN ISO 9001 -
- UNI EN ISO 14001 -

Sherwin-Williams Italy S.r.l. – con unico socio
Sede Legale ed Amministrativa
Via del Fiffo, 12 - 40065 Pianoro (BO) - Italia - C.P. 18
tel. +39 051 770 511 - fax +39 051 777 437
www.sayerlack.com
Cod. Fisc. e Reg. Impr. Bo 08866930152
P. IVA: IT 00494251200 - R.E.A. n. 313180
Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531
Società soggetta a direzione e coordinamento di The Sherwin-Williams Company, USA

АРТИКУЛ	СРОК ХРАНЕНИЯ	СУХОЙ ОСТАТОК	УДЕЛЬНАЯ ПЛОТНОСТЬ
	(месяцы)	%	кг/л
THL7111/00	24	36 ± 1	0,970 ± 0,030
THL7112/00	24	27 ± 1	0,920 ± 0,030
THL7170/00	24	30 ± 1	0,980 ± 0,030
THL7988/00	24	50 ± 1	1,010 ± 0,030
THV6332/00	24	37 ± 1	0,980 ± 0,030
THV7624/00	24	30 ± 1	0,990 ± 0,030
THV7764/00	24	55 ± 1	0,980 ± 0,030

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.
WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.